



devolo

dLAN® 1200+

Technical data

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3az, IEEE 802.1p Auto MDI/X
Protocols	CSMA/CA (Powerline)
Transmission speeds	Ethernet 10/100/1000 (mbps) Powerline 200/500/600/1200 (mbps)
Modulation • Carrier	Powerline OFDM - 4096/1024/256/64-QAM, QPSK, BPSK • Powerline 2880
Range (in m)	Powerline: 400
Security	128 Bit AES
LEDs	dLAN (multi)
Buttons	Pairing
Socket • Connector • Countries	Type G (BS 1363) • Type G (BS 1363) • (UK)
Power output to integrated socket	13 A
Device port	1 x Ethernet RJ45
Power consumption	Maximum W/A: 5.3 Typical W/A: 4.1 Stand-By W/A: 0.7
Power supply	internal 196-250 V AC 50 Hz
Attenuation filter	2 - 68 MHz
Filter characteristics	-22 db to -45 db
Temperature (Storage • Operating)	-25°C to 70°C • 0°C to 40°C
Dimensions (in mm, without plug)	130 x 66 x 42
Ambient conditions	10-90% Humidity (non-condensing)
Operating systems	Windows 7 (32/64 Bit) or higher Ubuntu-Linux MAC OS X 10.6 or higher iOS Android
Certifications	CE, UKCA

Version 31.01.2022



devolo

dLAN® 1200+

Sales information

Warranty (in years)	3
Accessories	Printed Install Flyer Ethernet Cable(s)

Single adapter

Starter Kit

9371 (UK)		9378 (UK)	
EAN:	4250059693715	EAN:	4250059693784
Weight:	115 x 190 x 81 mm	Weight:	188.5 x 231 x 78.5 mm
Dimensions:	380 g	Dimensions:	710 g
WEEE additional information:		WEEE additional information:	
Weight WEEE:	255 g	Weight WEEE:	510 g
Paper (Green Dot):	100 g	Paper (Green Dot):	165 g
Plastic (Green Dot):	2 g	Plastic (Green Dot):	4 g
other (Green Dot):	0.2 g	other (Green Dot):	0.4 g

© 2022 devolo AG, Germany. All rights reserved.
Technical data subject to change without notice.

Version 31.01.2022